

Effective **solution**
for longtime
storage

ULTRA DRY

≤ 0.5 % RH

Ø ≤ 1 % RH

max. 40 °C

MP DRY CABINET LT



elektronik



MP DRY CABINET I LT

EXTERNAL DIMENSIONS 700 x 960 x 680 mm
INTERNAL DIMENSIONS 600 x 760 x 500 mm
VOLUME 230 l

3 ESD shelves, adjustable in steps of 20 mm

MP DRY CABINET II LT

EXTERNAL DIMENSIONS 700 x 1920 x 680 mm
INTERNAL DIMENSIONS 600 x 1520 x 500 mm
VOLUME 460 l

5 ESD shelves, adjustable in steps of 20 mm

MP DRY CABINET IV LT

EXTERNAL DIMENSIONS 1410 x 1920 x 680 mm
INTERNAL DIMENSIONS 1200 x 1520 x 500 mm
VOLUME 920 l

10 ESD shelves, adjustable in steps of 20 mm

DRY CABINET LT SPECIFICATIONS

STANDARD CONFIGURATION			
FULL ESD BODY - RAL7016	✓	USB CONNECTOR	✓
MECHANICAL DOOR LOCK	•	ELECTROMAGNETIC DOOR LOCK	•
RADIAL FAN	✓	ADDITIONAL DRY UNIT MPDRY (FOR II + IV)	•
ADJUSTABLE HEATING UP TO 40 °C	•	HEIGHT-ADJUSTABLE LEGS	✓
DRYING UNIT MP DRY < 0.5 % RH	✓	ESD WHEELS	✓
ROTRONIC SENZOR ± 0.8 % RH, 0.1K	✓	CONFIGURABLE ACOUSTIC ALARM *	✓
FULLY GRAPHICAL TOUCH DISPLAY - IDEC	✓	INTERIOR LED ILLUMINATION	•
LAN NETWORK CONNECTION	•	STATUS LIGHT	•
INTEGRATED DATALOGGER - user configurable	✓	ROTRONIC SENZOR HPS ± 0.5 % RH, 0.1K	•

• optional accessories

* open door alarm, time defined by user
alarm for nonfunctional drying unit

www.dry-cabinet.com | www.drycabinet.eu

MP Elektronik Technologie, s.r.o. | Dlouhá 219 | 678 01 Blansko - Klepačov | Czech Republic
 Tel: +420 516 416 937 | Fax: +420 516 417 641 | E-mail: info@mpelektronik.cz | www.mpelektronik.cz